

SPECIFICATIONS

Bring Collaborative Touch to Any Display



PRODUCT	DTEN GO
SOFTWARE	DTEN OS
DISPLAY	HDMI Output (Any Size Display)
PLACEMENT	Mount on TV or below
CAMERA SYSTEM	4 Camera Array Up to 32ft (10m) video coverage Up to 160 degree horizontal field of view (HFOV)
AUDIO SYSTEM	HDMI & 3.5mm Audio Output Acoustic Echo Cancellation Automatic Gain Control (AGC) AI-based Noise Cancellation
NETWORK	Ethernet (RJ-45) WiFi 2.4Ghz & 5Ghz IPv4 Dynamic Host Configuration Protocol (DHCP)/ Static HTTP/HTTPS Proxy Support
INPUTS AND OUTPUTS	Ethernet LAN (RJ45) x 1 3.5mm Audio Jack x 1 HDMI Out x 1
IN THE BOX	DTEN GO Power cord and adapter HDMI cable x 1 Ethernet cable x 1 Quick start guide
POWER	100 to 240 VAC, 50 to 60 Hz
PRODUCT DIMENSIONS (H x W x D)	10.7 x 2.1 x 2.75 in (272 x 54 x 69mm)
PRODUCT WEIGHT	1.3 lb (0.6kg)
PACKAGING DIMENSIONS (H x W x D)	12.7 x 10.7 x 2.25 in (320 x 272 x 57mm)
PACKAGING WEIGHT	3.55lb (1.61kg)
OPERATING TEMPERATURE AND HUMIDITY	Operating Temperature 0°C to 40°C Storage Temperature -10°C to 60°C Operating Humidity 20% to 80% RH Storage Humidity 10% to 60% RH

PRODUCT	DTEN MATE
SOFTWARE	DTEN Mate OS
DISPLAY	LED 10.1" Capacitive Multi-touch Display
PLACEMENT	On table or handheld
AUDIO SYSTEM	Integrated Speaker
NETWORK	WiFi 2.4Ghz & 5Ghz
INPUTS AND OUTPUTS	Type-C x 1
IN THE BOX	DTEN Mate Power cord and adapter
POWER	100 to 240 VAC, 50 to 60 Hz
PRODUCT DIMENSIONS (H x W x D)	9.38 x 5.8 x 1.0 in (240 x 148 x 25 mm)
PRODUCT WEIGHT	1 lb (0.45kg)
PACKAGE DIMENSIONS (H x W x D)	12.6 x 6.8 x 1.5 in (320 x 173 x 38mm)



Be Present Anywhere

*Images are not in 1:1 ratio
**Specifications are subject to change without prior notice

Version 1.2.0